



# The Culligan Side Mount (CSM™) Series Heavy-Duty Water Filter System



## EXAMPLES OF MARKETS SERVED:

CLINICS  
EDUCATIONAL FACILITIES  
ENERGY & POWER  
FOOD & BEVERAGE PRODUCTION  
FOOD SERVICE/RESTAURANTS  
GROCERY  
HEALTHCARE/HOSPITALS/BIO-PHARMACEUTICAL  
HOSPITALITY/LODGING  
MANUFACTURING  
MUNICIPAL DRINKING WATER  
OIL & GAS

## High-Volume Filtration for Commercial and Industrial Water Systems

When you want to produce high quality water in a demanding and variable environment, trust Culligan filters. The Culligan Side Mount (CSM) heavy-duty filter reduces contaminants\* and solids that affect water quality and equipment efficiency. The Culligan-exclusive Smart Controller makes it easy for you to set up and manage your water treatment. Using optional accessories such as an automatic timer or sensors, monitor the system and filter as needed without constant supervision, saving resources and money.

The CSM heavy-duty commercial filter is part of the Culligan Matrix Solutions™ that combine durable and efficient equipment, systems experience, and technical experts who understand your unique requirements. From planning your system to installing your water treatment equipment, Culligan Matrix Solutions offer options that help deliver the quality of water to meet your needs. Contact Culligan today to discuss your water treatment options.

\*contaminants are not necessarily in your water.

## Culligan Matrix Solutions Advantages:

- Simple System Integration
- Global Product Platform
- Flexible Configurations
- Quick Delivery/Easy Installation
- Exclusive Culligan Advanced Electronics
  - Historical Operating Data
  - Alarm Recognitions
  - US Standard and Metric Readings
  - Remote Monitoring Options
  - Telemetry Options



**Pre-Treatment  
Solutions**



**Membrane  
Solutions**



**Deionization  
Solutions**



**Storage  
Solutions**



**Distribution  
Solutions**

## Warranty

Culligan's CSM water filters are backed by a limited 1-year warranty against defects in material, workmanship and corrosion. In addition, tanks carry a limited 5-year warranty.†

† See printed warranty for details. Culligan will provide a copy of the warranty upon request.

## System Specifications

Specification	US	Metric
Inlet Pressure (dynamic)	30–100 psig	207–690 kPa
Power Voltage Frequency Phase	120 Volts 50/60Hz	
Feed Water Temperature	40–120° F	4–49° C

1 120 Volt/ 24 Volt Cal./UL listed transformer included.

## Examples of Filter Applications

- Food and Beverage—Improved taste and increased cost savings
- Drinking Water—Reduces turbidity and chlorine; improves taste and clarity
- Boilers—Turbidity reduction, reduce sludge buildup
- Light Industry Processes—Reduces particulate matter

- Pretreatment—For softeners, RO's and DI systems
- Vehicle Wash—Turbidity reduction
- Grocery/Retail—Quality water for aesthetics and help extend equipment life

## Standard Features

- Single or Multiple Tank Configurations
- Culligan's Smart Controller—More control over your equipment with programming and monitoring capabilities typically found in more expensive PLC controls, a variety of add-on options for advanced instrumentation and communication let you easily customize the system to help meet your needs
- Telemetric Capability
- Regeneration initiation by choice or combination of time clock, flow meter or differential pressure switch
- Carbon Filters—For reduction of organics (flow rates up to 48 gpm per tank), or chlorine (flow rates up to 96 gpm per tank)
- Depth Filters—Flow rates up to 145 gpm per tank

- Culligan's Multiport Valve—Guided perimeter designed diaphragm valves are smooth operating and free of water hammer, all valve parts are easily accessible in the design for ease of service
- Corrosion resistant tanks—Made of low carbon steel with epoxy interior lining and finish coat painted exterior

## Optional Features & Accessories

- Patented Progressive Flow—Culligan's Smart Controller can monitor flow demands, bringing additional tanks on-line or off-line as flows increase or decrease
- Differential Pressure Switch
- ASME Code Tanks
- Gauge Packages—Pressure gauges provided for mounting at the inlet and outlet connection
- Separate source regeneration kits
- Skid Mounted—Fully pre-piped and wired systems for single point field utility connection of inlet, outlet, drain and power supply
- Flow Measuring Devices—Available for volume based regeneration initiation
- Remote Display
- RS232, RS485, Modbus PLC Output

## CSM Water Filter System

Model	Depth Filters					
	Service Flow Rates <sup>1</sup>		Backwash Flow <sup>2</sup> (gpm/lpm)	Pipe Size (in./mm)	Media Qty. (lbs./kg)	Filter Tank Size (in./mm)
	Normal gpm @ psi drop lpm @ kPa drop	Peak gpm @ psi drop lpm @ kPa drop				
CSM-202D	22 @ 6	33 @ 12	30	2	571	20 x 54
	83.3 @ 41.4	124.9 @ 13.8	113.6	50.8	259	508 x 1,372
CSM-242D	32 @ 5	48 @ 9	45	2	830	24 x 54
	121.1 @ 34.5	181.7 @ 62	170.3	50.8	376	610 x 1,372
CSM-302D	50 @ 9	74 @ 17	75	2	1244	30 x 60
	189.3 @ 62	280.1 @ 117	283.9	50.8	564	762 x 1,524
CSM-362D	71 @ 11	107 @ 23	105	2	1765	36 x 60
	268.7 @ 6.9	405 @ 159	397.4	50.8	801	914 x 1,524
CSM-422D	97 @ 15	145 @ 28	150	2	2488	42 x 60
	367.1 @ 103.4	548.8 @ 193	567.8	50.8	1129	1,067 x 1,524
CSM-423D	97 @ 6	145 @ 11	150	3	2488	42 x 60
	367.1 @ 41.4	548.8 @ 76	567.8	76.2	1129	1,067 x 1,524

<sup>1</sup> Service flow rates are based on:  
Normal (10 gpm/ft<sup>2</sup> - 24 m<sup>2</sup>/hr/m<sup>2</sup>) - Best quality effluent at specified flow. Lowest pressure loss. Recommended for suspended solids loads up to and greater than 300 ppm.  
Peak (15 gpm/ft<sup>2</sup> - 37 m<sup>2</sup>/hr/m<sup>2</sup>) - Very good quality effluent at specified flow. Increased pressure loss. Recommended for suspended solids loads < 300 ppm.  
<sup>2</sup> Backwash flow rates are based on 12-14 gpm/ft<sup>2</sup> (29-34 m<sup>2</sup>/hr/m<sup>2</sup>) using 50° F (10° C) water. A different backwash rate may be required depending upon water temperature.

Model	Carbon Filters					
	Service Flow Rates		Backwash Flow <sup>3</sup> (gpm/lpm)	Pipe Size (in./mm)	Media Qty. (ft <sup>2</sup> /m <sup>2</sup> )	Filter Tank Size (in./mm)
	Taste Odor & Organic Removal <sup>1</sup> gpm @ psi drop lpm @ kPa drop	Dechlorination <sup>2</sup> gpm @ psi drop lpm @ kPa drop				
CSM-242R	16 @ 3	31 @ 6	30	2	8	24 x 54
	60.6 @ 20.7	117.3 @ 41.4	113.6	50.8	0.227	610 x 1,372
CSM-302R	25 @ 4	49 @ 7	45	2	12	30 x 60
	94.6 @ 27.6	185.5 @ 48.3	170.3	50.8	0.34	762 x 1,524
CSM-362R	35 @ 3	71 @ 11	70	2	18	36 x 60
	132.5 @ 20.7	268.7 @ 6.9	265	50.8	0.51	914 x 1,524
CSM-422R	48 @ 4	96 @ 13	95	2	24	42 x 60
	181.7 @ 27.6	363.4 @ 20.7	359.6	50.8	0.68	1,067 x 1,524

<sup>1</sup> Service flow rates for taste, odor & organic removal are based on 5 gpm/ft<sup>2</sup> (12 m<sup>2</sup>/hr/m<sup>2</sup>).  
<sup>2</sup> Service flow rates for dechlorination are based on 10 gpm/ft<sup>2</sup> (24 m<sup>2</sup>/hr/m<sup>2</sup>).  
<sup>3</sup> Backwash flow rates are based on 10 gpm/ft<sup>2</sup> (24 m<sup>2</sup>/hr/m<sup>2</sup>) using 50° F (10° C) water. A different backwash rate may be required depending upon water temperature or the type of carbon used.  
NOTE: Operational, maintenance and replacement requirements are essential for this product to perform as advertised. Specifications shown are for single models. Also available in multiple tank configurations.  
All pressure drop figures are based on new filter media and a water temperature of 60° F.  
Depth filters are capable of 10 micron effluent water quality, whereas all other filter types are capable of 40 micron effluent water quality.

Finally, an end-to-end solution from a single source.



Place your commercial and industrial water treatment needs in the hands of a global leader.

For over 70 years, Culligan has made better water. Our global network, comprised of 800+ dealers and international licensees in over 90 countries, is dedicated to addressing your water-related problems. As a worldwide leader in water treatment, our sales representatives and service technicians are familiar with the local water conditions in your area. Being global and local position us to deliver customized solutions to commercial and industrial water issues that affect your business and your bottom line.

[www.culliganmatrixsolutions.com](http://www.culliganmatrixsolutions.com) • 866-787-4293

RR Donnelley # 46957 Print 02/10 ©2010 Culligan International Company.

All trademarks used herein are registered trademarks of Culligan International Company. Products manufactured or marketed by Culligan and its affiliates are protected by patents issued or pending in the United States and other countries. Culligan reserves the right to change the specifications referred to in this literature at any time, without prior notice.



Printed on recycled paper